

Panneau de commande à distance (ROP)

AK-HRP1000

Panneau de commande à distance (ROP)



KEY FEATURES

- Panneau de commande à distance de type 1/4 de rack
- Écran de mesure LCD en couleur permettant la contrôle par interface graphique utilisateur ainsi que par PoE+ et IP
- Master Gain, température de couleur et Master Flare variables pouvant être assignés à un bouton utilisateur programmable
- Manette de commande pour contrôler l'iris / la poursuite
- Peut être utilisé avec un mélange de caméras studio et à distance Panasonic par connexion IP

**Dernières
mises à jour**

SPECIFICATIONS

| | |
|-------------------------------|--|
| Power Supply | 12 V DC (Power supply from camera: 10 V - 16 V DC) 42 V - 57 V DC (PoE power supply) |
| Power Consumption | 0.51 A (Power supply from camera: 10 V - 16 V DC) 0.15 A (PoE power supply) |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Humidity | 90% or less |
| Storage Temperature | -20°C to 60°C (-4°F to 140°F) |
| Weight | Approx. 1.7 kg (3.75 lb) |
| Dimensions (W x H x D) | 102 mm x 385 mm x 113 mm (4 inches x 15-3/16 inches x 4-7/16 inches) |
| Camera/CCU Control | Control signals (camera, CCU control) Power supply 16 V DC (when CCU connected)*4, 12 V DC (when camera connected)*4 |
| Maximum Cable Length | When camera connected: 20 m (65.7 ft) When CCU connected: 50 m (164 ft) |
| Note | *1: Depending on the setting, only one of them can be selected at one time. *2: The BB (black burst) signal and tri-level sync signal of the reference input are recognized automatically. *3: IP video cannot be transmitted when [CCU MODE] is set to [2160/23.98p], [2160/23.98PsF], [1080/23.98p], or [1080/23.98PsF]. *4: Can be provided from CCU |
| Compatibility | - |

URL: <https://business.panasonic.fr/camera-professionnelle/panneau-de-commande-a-distance/AK-HRP1000>

CONTACT

Web: <https://business.panasonic.fr/camera-professionnelle/contact-us>